

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number
WO 2005/066252 A3

(51) International Patent Classification⁷: C05F 7/02,
C08K 3/22, H01B 3/00, C09K 5/08

(74) Agent: OHIE, Kunihisa; Ohie Patent Office,
Selva-Ningyosho 6F, 14-6, Nihonbashi-Ningyocho,
2-chome, Chuo-Ku Tokyo 103-0013 (JP).

(21) International Application Number:
PCT/JP2005/000431

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 7 January 2005 (07.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-3377 8 January 2004 (08.01.2004) JP
60/535,806 13 January 2004 (13.01.2004) US
2004-85269 23 March 2004 (23.03.2004) JP

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): SHOWA
DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Mi-
nato-ku, Tokyo 105-8518 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): TSUZUKI, Hiroshi
[JP/JP]; c/o Showa Titanium Co., LTD., 3-1, Nishinomiya-
machi, Toyama-shi., Toyama, 931-8577 (JP). KOGOI,
Hisao [JP/JP]; c/o Showa Titanium Co., LTD., 3-1,
Nishinomiya-machi, Toyama-shi., Toyama, 931-8577 (JP).
TANAKA, Jun [JP/JP]; c/o SHOWA DENKO K.K., 13-9,
Shibadaimon 1-chome, Minato-ku, Tokyo 1058518 (JP).

Published:

— with international search report

(88) Date of publication of the international search report:
26 January 2006

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: INORGANIC POWDER, RESIN COMPOSITION FILLED WITH THE POWDER AND USE THEREOF

(57) Abstract: The present invention relates to an inorganic powder having a frequency-size distribution with multiple peaks, wherein the peaks are present at least in the particle size regions from 0.2 to 2 μm and from 2 to 63 μm , preferably with the maximum particle size being 63 μm or less, the average particle size being from 4 to 30 μm , and the mode size being from 2 to 35 μm . The inorganic powder of the present invention is useful as a filler for a high thermally conductive member in electronic component-mounted circuit board required to have electrical insulating property and heat radiating performance, in that a heat radiating member comprising the powder can have thermal conductivity, the powder can provide a resin composition having excellent withstand voltage characteristics for forming an insulative composition into a thin film and can be filled in the resin composition at a high density so as to improve heat radiating performance of the resin composition.

WO 2005/066252 A3